FLOW CHARACTERISTICS AND MASS BALANCES OF A FULL SCALE VERTICAL FLOW CONSTRUCTED WETLAND

RENNIA MWENJE

BEng IN CHEMICAL ENGINEERING

SUPERVISORS

PROF C.A. BUCKLEY

DR G. ADHANOM

MS P. ARUMUGAM

AIM OF STUDY

- To determine the problems with the existing VFCW
- To recommend remediation on the VFCW
- To monitor the VFCW after remediations

RESEARCH QUESTIONS

- 1. Is the VFCW performing efficiently?
- 2. Is the HLR sufficient?

OBJECTIVES

FULL SCALE

- To monitor flow distribution onto the VFCW
- To measure effects of evapotranspiration
- To determine nutrient removal efficiency

BACKGROUND OF STUDY

- The DEWAT plant is located at Newlands,
 Durban
- VFCW forms part of a DEWAT polishing step
- Plant has been operational since 2010
- Property of eThekwini municipality
- Used as a research site by students from UKZN, DUT and international students
- Designed according to BORDA standards to treat domestic wastewater from 84 households




WHAT IS A DEWAT SYSTEM?

- Historically centralised WWTPs have been used to treat wastewater
- However, population growth exerts pressure on WWTPs alternatives like DEWATS are being used
- DEWATS are decentralised wastewater treatment systems


Advantages of DEWATS

- Appropriate for low population communities
- Have less energy requirements
- Require less, capital, operational and transport costs



CONSTRUCTED WETLANDS

- Mimic natural wetlands by making use of microorganisms, plants and filter media
- Remove pollutants through physical, chemical and biological processes




WHY CONSTRUCTED WETLANDS?

- Low operational and maintenance costs
- High tolerance on load and flow
- Few impacts on the environment
- Habitant for organisms
- Aesthetic appearance




VERTICAL FLOW CONSTRUCTED WETLANDS

- Are intermittently fed creating aerobic and anaerobic conditions
- Water flows vertically down





DISTRIBUTION SYSTEM







FULL SCALE FLOW CHARACTERISTICS







FULL SCALE INFLUENT AND EFFLUENT CONCENTRATIONS











FULL SCALE MASS BALANCES





PROBLEMS ASSOCIATED WITH FULL SCALE VFCW

- Inconsistent operation of the siphon
- Poor layout of the distribution pipes
- Incorrect construction of the VFCW outlet sump
- These problems lead to construction of pilot trials and remediation on the distribution pipes

PILOT SCALE VFCWS

- Different media types
- Increased depth
- Controlled influent distribution
- Outlet flow rate measurements





FUTURE WORK

• Monitoring of effluent chemical parameters after remediation

SIPHON AND VFCW AFTER REMEDIATION







- VFCW operating under low HLR
- Underutilisation of the VFCW bed
- Effluent not meeting discharge limits
- VFCW acting as a nitrifying bed

REFERENCES

- 1. GUTTERER B, SASSE L, PANZERBIETER T and RECKERZÜGEL T (2009)

 Decentralised wastewater treatment systems (DEWATS) and sanitation in developing countries. Leicestershire, UK: Water, Engineering and Development Centre (WEDC), Loughborough University, UK, in association with Bremen Overseas Research (BORDA), Germany.
- 2. KADLEC RH and WALLACE SD (2009) *Treatment wetlands*, CRC Press, Boca Raton, FL.
- 3. LEE S, MANIQUIZ-REDILLAS MC, CHOI J and KIM L-H (2014) Nitrogen mass balance in a constructed wetland treating piggery wastewater effluent. *Journal of Environmental Sciences* **26** (6) 1260-1266.
- 4. STEFANAKIS A, AKRATOS CS and TSIHRINTZIS VA (2014) Vertical flow constructed wetlands: Eco-engineering systems for wastewater and sludge treatment, Newnes.



Thank you